F75P – 3U CompactPCI® PlusIO Safe Railway Computer

- **2x Intel® Atom™ E6xx, 512 MB DDR2 RAM (each) for onboard dual redundancy**
- **1x Intel® Atom™ E6xx, 1 GB DDR2 for I/O**
- **Independent supervisors for each block**
- **Fail-safe and fail-silent board architecture**
- **Clustering of two F75P to raise availability**
- **Event logging**
- **Certifiable up to SIL 4 (with report from TÜV SÜD)**
- **Developed according to EN 50129, EN 50128 and IEC 61508**
- **Full EN 50155 compliance**
- **-40 to +85°C qualified**
- **Conformal coating**

The F75P is a COTS safe computer with onboard functional safety that unites three CPUs on one 3U CompactPCI® PlusIO card. It makes Intel® Atom™ E6xx ("E600") performance with dual redundancy extremely compact, mainly targeting railway applications. Two independent Control Processors (CP) with independent DDR2 RAM and Flash and a supervision structure provide safety: with redundant software running on F75P, and, e.g., with the software instances on the two CPs comparing their output, the board becomes a fail-silent subsystem, i.e. it can shut down in case of a fatal fault.

Its I/O Processor (IOP) is built up like a classic CompactPCI® CPU board, including DDR2 RAM, front and rear I/O. The front connectors include VGA, two USB 2.0, and two 100-Mbit (Fast) Ethernet channels. At the rear, the board provides another four USB 2.0, two Fast Ethernet ports, one 3-Gbit SATA and one PCI Express® x1 link. These interfaces comply with the standardized pinout of CompactPCI® PlusIO (PICMG 2.30). An onboard mSATA slot makes for scalable, robust mass storage. The intelligent board management controller of the IOP logs events such as reset, overvoltage or undervoltage in a non-volatile FRAM.

The Control (CP) and I/O Processors (IOP) communicate via internal links provided by an FPGA.

While the IOP also supports Windows®, the CPs are designed to run a deterministic real-time operating system such as the QNX® Neutrino RTOS Safe Kernel or PikeOS. It is also possible to implement diversitary software on both kernels. All three CPUs support Linux and QNX®.

The F75P can replace multiprocessing systems with CPU redundancy and I/O by a small-footprint, low-power solution that is flexible for different types of application scenarios. It uses a single +5V supply voltage to allow operation with external power supplies that do not generate +3.3 V.

A clustering option is considered as well, to increase system availability: two F75P boards can operate next to each other, and can provide hot or cold stand-by.

F75P-based systems are generally certifiable up to SIL 4. Since the card has no voter of its own, the customer has to add the software that implements and controls functional safety behavior. The safety features such as the CP supervisors are designed to SIL 4 according to EN 50129. A railway certification package including the "safety case" document and a certificate from TÜV SÜD is available.

Its rugged set-up also make the F75P truly rail-ready: with assets like conformal coating and an operating temperature of -40 to +85°C with qualified components, it is fully EN 50155 compliant. A 4-HP version is available with RJ45 Ethernet connectors and a reduced temperature range for system design, while another standard card with 8 HP width provides the necessary space for M12 front connectors and a larger heat sink for -40 to +85°C.

Diagram


Safe Domain
Power Control
Supervisor
Supervisor
DDR2 SDRAM
Control Processor 1 (CP1)
Intel® Atom™ E6xx
Control Processor 2 (CP2)
Intel® Atom™ E6xx
DDR2 SDRAM
BIOS Flash
BIOS Flash
PCIe x1
PCIe x1
F Reset
Supervisor
Inter-Communication FPGA (ICOM)
PCIe x1
F Fast Ethernet
F Fast Ethernet
F Status LED
FRAM
BMC Board Management
Fast Ethernet
Fast Ethernet
Cluster Link
CPCI J2
F VGA
F USB 2.0
F USB 2.0
I/O Processor (IOP)
Intel® Atom™ E6xx
EG20T PCH
PCI Express (2.5 Gb)
SATA (3 Gb)
USB 2.0
R
PCIe to PCI
CPCI J1
R
BIOS Flash
DDR2 SDRAM
mSATA
B
F Front panel
R Rear side
B Onboard

Technical Data

CPU Architecture	■ Three onboard processors □ Two Control Processors (CP) □ One I/O Processor (IOP) □ Inter-communication between all three processors via onboard Ethernet or Shared RAM ■ Three identical processor types □ Intel® Atom™ E6xx Series □ 0.6 GHz to 1.6 GHz processor core frequency □ Please see Standard Configurations and Options below for options and available standard versions. ■ Main function of CPs □ Provide a "Safe Domain" on the board, including processors, memory, supervisors and power control □ Provide flexible implementation options for functional safety requirements □ Provide support for advanced, certified operating systems up to SIL 4 ■ Main function of IOP □ Provide common I/O and memory facilities □ Provide a user-friendly software interface and GUI
Memory (connected to CPs)	■ 512 KB L2 cache integrated in E6xx for each processor ■ Up to 1 GB SDRAM system memory to each of the Control Processors (CP) □ Soldered □ DDR2 □ 800 MHz memory bus frequency (800 MT/s data rate) ■ 2 MB BIOS Flash ■ Please see Standard Configurations and Options below for options and available standard versions.
Chipset (connected to IOP)	■ Intel® EG20T Platform Controller Hub (PCH)
Memory (connected to IOP)	■ 512 KB L2 cache integrated in E6xx ■ Up to 2 GB SDRAM system memory □ Soldered □ DDR2 □ 800 MHz memory bus frequency (800 MT/s data rate) ■ 2 MB BIOS Flash ■ 8 KB non-volatile FRAM for event logging ■ mSATA disk slot □ Connected via one SATA channel □ For IOP boot image and file system ■ Please see Standard Configurations and Options below for options and available standard versions.
Mass Storage (connected to IOP)	■ Serial ATA (SATA) □ One port for mSATA onboard devices □ One port for rear I/O □ SATA Revision 2.x support □ Transfer rates up to 300 MB/s (3 Gbit/s)
Graphics (connected to IOP)	■ Integrated in E6xx processor □ 320 or 400 MHz graphics base frequency, depending on processor type □ Maximum resolution: 1280 x 1024 pixels ■ VGA connector at front panel

Technical Data

I/O (controlled by IOP)	■ USB □ Six USB 2.0 host ports □ Two Series A connectors at front panel □ Four ports via rear I/O on CompactPCI® J2 □ OHCI and EHCI implementation □ Data rates up to 480 Mbit/s ■ Ethernet □ Four 10/100Base-T Ethernet channels, via Inter-Communication FPGA □ Two channels via RJ45 or M12 connectors at front panel, with status LEDs □ Two channels via rear I/O on CompactPCI® J2 ■ PCI Express® □ One PCI Express® x1 link via rear I/O on CompactPCI® J2 □ PCIe® 1.0a support □ Data rate up to 250 MB/s in each direction (2.5 Gbit/s per lane)
Front Connections (Standard)	■ VGA ■ Two USB 2.0 (Series A) ■ Two 10/100Base-T Ethernet (RJ45 or M12)
Rear I/O (PICMG 2.30)	■ One SATA (3 Gb) ■ Four USB 2.0 ■ Two 10/100Base-T Ethernet ■ One PCI Express® x1 link ■ Compatible with PICMG 2.30 CompactPCI® PlusIO □ 1PCI33/1PCIE2.5/1SATA3/4USB2/2ETH100 □ Some pins are used for signals differing from the PICMG 2.30 specification, e.g., for clustering. However, these signals do not destroy or cause any malfunction of a connected I/O board based on this standard.
Event Logging	■ Event history logged in non-volatile FRAM, e.g., reset, overvoltage, undervoltage, excess temperature ■ 256 entries possible ■ Events are generated by board hardware or user application
Cluster Link	■ Two F75P boards can be connected to form a cluster ■ Cluster link interface based on RS422 □ Accessible on CompactPCI® J2 rear I/O connector □ Bidirectional, full-duplex, differential interface
Miscellaneous	■ Real-time clock with supercapacitor backup connected to I/O Processor □ Data retention of supercapacitor: minimum 72 hours when fully loaded ■ Three independent supervisors for Control Processors and Inter-Communication FPGA □ Check for overvoltage, undervoltage, excess temperature, internal errors of FPGA and CPUs, CPU and FPGA clock □ Watchdog ■ Board Management Controller for I/O Processor ■ Status LED at front panel ■ Reset button at front panel
CompactPCI® Bus	■ Compliance with CompactPCI® Core Specification PICMG 2.0 R3.0 ■ System slot ■ 32-bit/33-MHz PCI-to-PCI bridge ■ V(I/O): +3.3 V (+5 V tolerant) ■ Hot insertion and removal without damage
Busless Operation	■ Board can be supplied with +5 V only, all other voltages are generated on the board ■ Backplane connectors used only for power supply
Electrical Specifications	■ Supply voltage/power consumption: □ +5 V (-5%/+5%), tbd. A

Technical Data

Mechanical Specifications	■ Dimensions: conforming to CompactPCI® specification for 3U boards ■ Front panel: 4 HP or 8 HP with ejector ■ Weight: □ 4 HP, RJ45 connectors: tbd. g (incl. heat sink) □ 8 HP, M12 connectors: tbd. g (incl. heat sink)
Environmental Specifications	■ Temperature range (operation): □ -40..+50°C in 4 HP version (qualified components) □ -40..+85°C in 8 HP version (qualified components), compliant with EN 50155, class Tx □ Conditions: airflow 1.5 m/s, typical power dissipation: tbd. ■ Temperature range (storage): -40..+85°C ■ Relative humidity (operation): max. 95% non-condensing ■ Relative humidity (storage): max. 95% non-condensing ■ Altitude: -300 m to +3000 m ■ Vibration (function): 1 m/s², 5 Hz - 150 Hz (EN 50155 (12.2.11) / EN 61373) ■ Vibration (lifetime): 7.9 m/s², 5 Hz - 150 Hz (EN 50155 (12.2.11) / EN 61373) ■ Shock: 50 m/s², 30 ms (EN 50155 (12.2.11) / EN 61373) ■ Conformal coating (standard)
MTBF	■ 290 331 h @ 40°C according to IEC/TR 62380 (RDF 2000)
Safety	■ Functional Safety □ Certifiable up to SIL 4 according to EN 50129 ("safety case" document and certificate from TÜV SÜD available) □ Hazard rate for safety functions <= 1E-9 / h □ Control Processors configured for deterministic behavior, e.g., Hyper-Threading disabled, speed-step disabled, BIOS interrupts disabled □ Board maintains safe state after a failure (factory configuration) ■ Flammability □ PCB manufactured with a flammability rating of 94V-0 by UL recognized manufacturers
EMC Conformity	■ When integrated into an EMC protected rack ■ EN 50121-3-2 (tables 5 and 6) / EN 55011 (radio disturbance) ■ EN 50121-3-2 (table 9) / IEC 61000-4-6 (ESD) ■ EN 50121-3-2 (table 9) / IEC 61000-4-3 (electromagnetic field immunity) ■ EN 50121-3-2 (table 8) / IEC 61000-4-4 (burst) ■ EN 50121-3-2 (table 8) / IEC 61000-4-6 (conducted disturbances)
BIOS	■ InsydeH2O™ UEFI Framework
Software Support	■ I/O Processor □ Windows® 7 □ Windows® Embedded Standard 7 (in preparation) □ Linux (in preparation) □ QNX® (in preparation) ■ Control Processors □ QNX® (with or without Safe Kernel) (in preparation) □ PikeOS □ Linux (in preparation) □ VxWorks® (on request) □ VxWorks®/Cert (on request) ■ For more information on supported operating system versions and drivers see Downloads.

Configuration & Options

Standard Configurations

Article No.	CPU Type	System RAM	Ethernet connectors	Front Panel	Conformal Coating	Operating Temperature
02F075P00	3x E680T, 1.6 GHz	CPs: 512 MB each, IOP: 1 GB	RJ45	4 HP	Yes	-40..+50°C qualified
02F075P01	3x E680T, 1.6 GHz	CPs: 512 MB each, IOP: 1 GB	M12 (right)	8 HP	Yes	-40..+85°C qualified

Options

CPU	■ Intel® Atom™ E620T, 0.6 GHz, 320 MHz graphics frequency, 3.3 W TDP (estimated) ■ Intel® Atom™ E640T, 1.1 GHz, 320 MHz graphics frequency, 3.6 W TDP ■ Intel® Atom™ E660T, 1.3 GHz, 400 MHz graphics frequency, 3.6 W TDP ■ Intel® Atom™ E680T, 1.6 GHz, 400 MHz graphics frequency, 4.5 W TDP (estimated)
Memory	■ System RAM □ 512 MB or 1 GB for each Control Processor □ 1 GB or 2 GB for I/O Processor ■ mSATA disk □ 0 MB up to maximum available
I/O	■ Ethernet □ RJ45 or M12 connectors □ M12 connectors need a second front-panel slot (8 HP total width) and can be placed to the left or right side of the CPU PCB.
Operating Temperature	■ -40..+50°C (4 HP) ■ -40..+85°C (8 HP, with larger heat sink) ■ Depends on heat sink configuration
Coating	■ With or without conformal coating
Cooling Concept	■ Also available with conduction cooling in MEN CCA frame
Restart Option	■ Board can be configured to restart automatically after entering safe state (by factory configuration)
Software Support	■ VxWorks® for Control Processors (on request) ■ VxWorks®/Cert for Control Processors (on request)

Please note that some of these options may only be available for large volumes. Please ask our sales staff for more information.

Ordering Information

Standard F75P Models	**02F075P00**	3x Intel® Atom™ E680T (1.6 GHz), 2x 512 MB, 1x 1 GB DDR2 DRAM, RJ45 ETH connectors, 4 HP, -40..+50°C with qualified components, conformal coating
	02F075P01	3x Intel® Atom™ E680T (1.6 GHz), 2x 512 MB, 1x 1 GB DDR2 DRAM, 8 HP, Ethernet on the right by 2x M12, -40..+85°C with qualified components, conformal coating
Related Hardware	**08CT12-00**	CompactPCI® PlusIO rear transition module 3U/80mm, 2 Ethernet, 4 USB, 4 SATA, 4 PCIe® x1, -40°C..+85°C qualified
Memory	**0751-0051**	SSD mSATA, 8 GB, -40..+85°C
Certification Packages	**23F075P00**	SIL 4 railway certification package according to EN 5012x for F75P, including: Safety User Guide including the safety-relevant application requirements, a detailed description of the hardware and instructions for appropriate operation. Safety Case describing the concepts for reaching functional safety as well as all safety and quality-relevant processes and measures to meet the SIL 4 requirements. Assessment report and SIL 4 certificate from TÜV SÜD (German Technical Inspection Agency). 40 hours support Please contact us to get more information about the certification package and to request a copy of the documents.
	For more information on the F75P certification packages, see this introductory overview presentation (PDF).	
	23F075P40	SIL 4 railway certification package according to EN 5012x for F75P with QNX®, including: Safety User Guide including the safety-relevant application requirements, a detailed description of the F75P/QNX® hardware/software package and instructions for appropriate operation of the HW/SW package. Safety Case describing the concepts for reaching functional safety as well as all safety and quality-relevant processes and measures to meet the SIL 4 requirements. Assessment report and SIL 4 certificate from TÜV SÜD (German Technical Inspection Agency) covering the F75P/QNX® hardware/software bundle. 90 hours support Please contact us to get more information about the certification package and to request a copy of the documents.
Systems & Card Cages	**0701-0046**	CompactPCI® 19" 4U/24HP desktop system for 3U cards, 3-slot 3U CompactPCI® backplane, system slot right, 1U fan tray with 1 fan, 8 HP space for 1 pluggable PSU
	0701-0056	CompactPCI® 19" 4U/84HP rack-mount enclosure for 3U cards (vertical), 4+4-slot 3U CompactPCI® / CompactPCI® Serial hybrid backplane, prepared for rear I/O, 250W power supply wide range 90..264VAC on rear, 1U fan tray with 2 fans included, 0..+60°C
Software: Windows®	This product is designed to work under Windows®. See below for potentially available separate software packages from MEN.	
	10Y000-78	Windows® Embedded Standard 7 BSP for F11S, F19P, F21P, F22P, F75P, G20, G22, XM1L, XM2, MM1, MM2, SC21, SC24, SC27, BC50M, BC50I, BL50W, BL50S, DC13, F206, F210, F215, F216, G215, P506, P507 and P511
	13Y018-70	Windows® 64-bit FPGA update tool (MEN)
Software: PikeOS	This product is designed to work under PikeOS by SYSGO. The PikeOS BSP is certifiable according to EN 50128 SIL 4 together with the F75P. PikeOS is a real-time operating system for use in safety and mission-critical systems. For more information please contact www.sysgo.com.	

For operating systems not mentioned here contact MEN sales.

Ordering Information

Documentation

Compare Chart 3U CompactPCI® Serial CPU and I/O cards » Download

Compare Chart safe computers from MEN » Download

Compare Chart 3U CompactPCI® / PlusIO CPU cards » Download

Compare Chart 3U CompactPCI® / PlusIO peripheral cards » Download

23F075P00	SIL 4 railway certification package according to EN 5012x for F75P, including: Safety User Guide including the safety-relevant application requirements, a detailed description of the hardware and instructions for appropriate operation. Safety Case describing the concepts for reaching functional safety as well as all safety and quality-relevant processes and measures to meet the SIL 4 requirements. Assessment report and SIL 4 certificate from TÜV SÜD (German Technical Inspection Agency). 40 hours support Please contact us to get more information about the certification package and to request a copy of the documents.

For more information on the F75P certification packages, see this introductory overview presentation (PDF).

23F075P40	SIL 4 railway certification package according to EN 5012x for F75P with QNX®, including: Safety User Guide including the safety-relevant application requirements, a detailed description of the F75P/QNX® hardware/software package and instructions for appropriate operation of the HW/SW package. Safety Case describing the concepts for reaching functional safety as well as all safety and quality-relevant processes and measures to meet the SIL 4 requirements. Assessment report and SIL 4 certificate from TÜV SÜD (German Technical Inspection Agency) covering the F75P/QNX® hardware/software bundle. 90 hours support Please contact us to get more information about the certification package and to request a copy of the documents.

For more information on the architecture of safe computer systems based on 3U CompactPCI®, please read our white paper Railway Computer 3.0: An Innovative Board Design Could Revolutionize The Market, available in English and German. » Download

Contact Information

Germany

MEN Mikro Elektronik GmbH
Neuwieder Straße 3-7
90411 Nuremberg
Phone +49-911-99 33 5-0
Fax +49-911-99 33 5-901

info@men.de
www.men.de

France

MEN Mikro Elektronik SAS
18, rue René Cassin
ZA de la Châtelaine
74240 Gaillard
Phone +33 (0) 450-955-312
Fax +33 (0) 450-955-211

info@men-france.fr
www.men-france.fr

USA

MEN Micro Inc.
860 Penllyn Blue Bell Pike
Blue Bell, PA 19422
Phone (215) 542-9575
Fax (215) 542-9577

sales@menmicro.com
www.menmicro.com

The date of issue stated in this data sheet refers to the Technical Data only. Changes in ordering information given herein do not affect the date of issue. All brand or product names are trademarks or registered trademarks of their respective holders.
MEN is not responsible for the results of any actions taken on the basis of information in the publication, nor for any error in or omission from the publication.
MEN expressly disclaims all and any liability and responsibility to any person, whether a reader of the publication or not, in respect of anything, and of the consequences of anything, done or omitted to be done by any such person in reliance, whether wholly or partially, on the whole or any part of the contents of the publication.
The correct function of MEN products in mission-critical and life-critical applications is limited to the environmental specification given for each product in the technical user manual.The correct function of MEN products under extended environmental conditions is limited to the individual requirement specification and subsequent validation documents for each product for the applicable use case and has to be agreed upon in writing by MEN and the customer.Should the customer purchase or use MEN products for any unintended or unauthorized application, the customer shall indemnify and hold MEN and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim or personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that MEN was negligent regarding the design or manufacture of the part.
In no case is MEN liable for the correct function of the technical installation where MEN products are a part of.

Copyright © 2014 MEN Mikro Elektronik GmbH. All rights reserved.